

TXA-620CD

Portable amplifier system, with integrated wireless receiver and CD player with "anti-shock system".

USB INPUT



Carry case:



Built in CD & radio microphone:

TXA-620CD:

Operation via mains connection or built-in rechargeable lead gel battery 12V/7Ah (operating time: up to 8 hours), integrated automatic charging of rechargeable battery

Ideally suited for mobile applications at sales events, lectures, etc.

High-quality CD player with slot-in mechanism, USB connection for external storage media, reproduction of audio CDs, CD-Rs

2-way speaker system

2 inputs (channels 1+2) via comb. jacks mic (XLR)/line (6.3mm), gain controls, 2-way tone control

2 stereo line inputs (channels 3+4) via RCA jacks, gain controls, common 2-way tone control Adjustable talkover

Link connections (2 x 6.3mm jack) for the combination of several amplifier systems TXA-610CD, TXA-620CD, or TXA-600

6.3mm jack connection (4ohm) for external speaker TXB-600

Stand sleeve

Supplied with remote control

Supplied with practical protective shoulder bag; the bag can stay on during operation

2-way system Frequency range: 60-18,500Hz Stand sleeve 6.3mm jack connection Supplied with practical protective shoulder bag; the bag can stay on during operation. Matching microphone transmitters or pocket transmitters are available at option, e.g. TXS-821HT, TXS-820HSE, TXS-820LT or TXS-820SX.

50 Watt system

Technical Facts Amplifiers

| | |
|-----------------------|--|
| Output power | 50W _{MAX} /36W _{RMS} |
| Frequency range | 60-18,500Hz |
| Carrier frequency | 863.05MHz |
| Range | approx. 30m |
| Mic inputs | 1.5mV |
| Line inputs | 150mV |
| Link | 650mV |
| Equalizer, bass | ±12dB/40Hz |
| Equalizer, treble | ±12dB/12kHz |
| Power supply | 230V~/50Hz/45VA, rech. battery: 12V/7Ah |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 235 x 450 x 280mm |
| Weight | 9.7kg |

Monacor TXA-620CD

Total cost excluding VAT & delivery £660.00

£787.30 inc vat & delivery



Tel 0161 872 7001
Fax 0161 872 7002

Avonics Ltd
Northstage
78 Broadway
Salford
M50 2UW

E-mail info@avonics.co.uk
Web www.avonics.co.uk



Monacor options



TXS-820SX = 863.05MHz
TXS-822SX = 864.80MHz

Headband Microphone with Transmitter

- * Electret headband microphone with 3.5mm plug with latching device.
- * Transmitting power: < 5mW (EIRP)
- * Min. range of 30m
- * Volume control, power LED, belt clip.
- * Power supply via 9V battery (not supplied).
- * Carrier frequency 863.05MHz or 864.80MHz
- * Dimensions 66x108x35mm
- * Weight 100g

TXS-820SX Headband microphone with transmitter

Total cost ex VAT = £65.00

Hand-held Microphones with Integrated Transmitter



- Dynamic, cardioid characteristic
- Switch for transmission mode, power LED
- Power supply via 9V battery (not supplied)
- Transmitting power: < 10mW (EIRP)
- Operating range: approx. 30m
- Carrier frequency 863.05MHz

TXS-821HT Hand-held Microphones with Integrated Transmitter

Total cost ex VAT = £65.00



TXB-600



Includes protective carry case for both items:

TXB-600 = Additional speaker suitable for the TXA-620CD

- * 2-way system
- * Frequency range: 60-18,500Hz
- * Stand sleeve
- * 6.3mm jack connection
- * Supplied with practical protective shoulder bag which can stay on during operation
- * Dimensions: 235 x 450 x 280mm Weight: 3.5kg

Monacor TXB 600 add on speaker

Total cost ex VAT =£160.00



P115XB Black High Quality Adjustable PA Speaker Stand With a 35mm Centre Pole. Maximum Load 20kg (Sold Individually) A high quality speaker stand made from aluminium and featuring a 35mm centre pole. Finished in black. Price per stand.

Dimensions 1000x150x150mm
Weight 2.6kg

Max Load Kg. 20
Height Adjustment 1000-1800mm

Optional speaker stands

Total cost ex VAT = £19.50 each



Tel 0161 872 7001
Fax 0161 872 7002

Avonics Ltd
Northstage
78 Broadway
Salford
M50 2UW

E-mail info@avonics.co.uk
Web www.avonics.co.uk

